

Ex-5516/ST/6h/MMSKV24 EMV-Z

Ex plug 16A 250V, brass, IP66



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



WISKA-Order no.

10030777

Type	Ex-5516/ST/6h/MMSKV24 EMV-Z
Material	Brass
Voltage	250 V
Voltage max. (V)	400 V
Type of Voltage	AC
Current	16 A
Protection class	IP56
plug insert	EXPORT
Clock face position	6h
Temp. range min	-40 °C
Temp. range max	40 °C
Type of cable gland	M 24 x 1,5
Ø cable diameter min	9 mm
Ø cable diameter max	17 mm
Type of cable	armoured
Marking	II 2 D Ex tb IIIC T65°C Db, II 2 G Ex de IIC T6...T5 Gb
Approval	TÜV 14 ATEX 7565X, IECEx TUR 15.0018X
Explosion Groups	IIIC, IIC
Temp.-class	T6
Zone	21, 1
Approval	DNV-GL, RMRS
Weight	1,3 kg
Tariff number	85366990

Remarks:

Your Contact:

WISKA America SRL

Mr. Alexander Bauer · Cervantes 911 c/Venezuela · Asunción · Paraguay

☎ +595-992-921719 · 📠 +49-4191-508-129

a.bauer@wiska.de · www.wiska.lat

- 6h - 2-pole + E, 220V-250V
- Flameproof enclosed interior
- Temperature range -40°C - +55°C = T5

Spare parts

SP-55161-ATEX Ex plug interior

22000415

06.08.2026

Your Contact:

WISKA America SRL

Mr. Alexander Bauer · Cervantes 911 c/Venezuela · Asunción · Paraguay

☎ +595-992-921719 · 📠 +49-4191-508-129

a.bauer@wiska.de · www.wiska.lat