

MFD 20/02/050

Multiple sealing insert



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.





| | |
|------------------------------|-------------------------|
| Material | Thermoplastic elastomer |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP66 / IP68 |
| Ø cable diameter min | 3 mm |
| Ø cable diameter max | 5 mm |
| Quantity of cable | 2 |
| BxL | 16,6 x 11,5 mm |
| Product Color | RAL 9005 |
| Using for cable gland | SPRINT 20 |
| Order no. RAL 9005 | 10101015 |
| Type | MFD 20/02/050 |
| Packing unit | 25 |
| ETIM-Classification | EC000441 |

Remarks:

IP68: Ø cable diameter min. = Ø cable diameter max. - 10%, but not bigger than 1 mm under the Ø cable diameter max.

IP66: 2 cables Ø 3 - 5 mm

16.04.2021

Your Contact:

WISKA America SRL

Mr. Alexander Bauer · Cervantes 911 c/Venezuela · Asunción · Paraguay

☎ +595-992-921719 · 📠 +49-4191-508-129

a.bauer@wiska.de · www.wiska.lat